

MATERIALS CHECKLIST

POLYGUARD[®] AIRLOK[®] STPE WRB SERIES

AIR BARRIER SYSTEM: ABOVE-GRADE STPE FLUID-APPLIED MEMBRANE

Polyguard Airlok[®] STPE WRB Spray-N-Roll

Airlok[®] Spray-N-Roll is a fluid-applied air & water-resistant barrier coating and is used over CMU, wood and gypsum sheathing. It can be applied in temperatures between 25°F (-3°C) to 110°F (49°C), at an application thickness of 23 mils wet, and a coverage rate of 69 SF per gallon. It is UV resistant up to 6 months.

Check		Part Number	Unit Size	Units/pallet	Wt/unit
	Polyguard Airlok[®] Spray-N-Roll	AIRLOK STPE 2300-5 GAL	5-gallon pail	36 pails/pallet	50#/pail
		AIRLOK STPE 2300-50 GAL	50-gallon drum	4 dr/pallet	540#/drum
	Airlok[®] STPE WRB System Components (where applicable):	Part Number	Unit Size	Units/pallet	Wt/unit
	Airlok [®] STPE WRB Flash-N-Roll	AIRLOK STPE 2400-2 GAL	2-gallon pail	64 pails/pallet	20#/pail
	Airlok [®] STPE WRB Flash-N-Roll	AIRLOK STPE 2400-5 GAL	5-gallon pail	36 pails/pallet	50#/pail
	Airlok [®] STPE WRB Gun-N-Spread	AIRLOK STPE 2100-SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
	Airlok [®] STPE WRB Detail-N-Joint	AIRLOK STPE 2200-SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
	Detail Sealant PW™ • 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
	Detail Sealant PW™ • 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3-gallon pail	36 pails/pallet	37#/pail
	<i>* Detail Sealant PW™ required in certain details – contact Polyguard Products.</i>				
	Possible Accessories:	Part Number	Unit Size	Units/pallet	Wt/unit
	Airlok [®] 200 BU/NP <small>- 28 mil (6", 9", 12", 18", 24") Commonly used as TWF</small>	varies/size	100' roll	36 ctns/pallet	6" to 18" • 75#/ctn 24" • 80#/ctn
	Airlok [®] UV 200 BU/NP <small>- 28 mil (6", 9", 12") Used as Window Flashing Only; no TWF</small>	varies/size	100' roll	36 ctns/pallet	75#/ctn
	Airlok [®] 400 NP <small>- 40 mil (6", 9", 12", 18", 24") Commonly used as TWF</small>	varies/size	75' roll	36 ctns/pallet	6" to 18" • 68#/ctn 24" • 76#/ctn
	Airlok [®] UV 400 NP <small>- 40 mil (6", 9", 12") Used as Window Flashing Only; no TWF</small>	varies/size	75' roll	36 ctns/pallet	68#/ctn
	Airlok [®] UV Ultra 400 NP <small>- 40 mil (6", 9", 12") Used as Window Flashing Only; no TWF</small>	varies/size	75' roll	36 ctns/pallet	68#/ctn
	<i>Choose product relative to specific application.</i>				
	650 LT Liquid Adhesive • 5 gal. pail	650-5 LIQ ADH 5 GA	5-gallon pail	36 pails/pallet	45#/pail
	650 LT Liquid Adhesive • 4 – 1 gal. pails	650-5 LIQ ADH 1 GA	4 – 1 gal pails/ctn	54 ctns/pallet	31#/ctn
	California Sealant	CALSEALS	5-gallon pail	36 pails/pallet	45#/pail

Weights listed are estimates.