





POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING OVER POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL OR 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL, INSTALL IN SHINGLE MANNER WITH MINIMUM 9" OVERLAP

CONCRETE SLAB

POLYGUARD DETAIL SEALANT PW OR LM-95 APPLIED AND TOOLED TO MINIMUM 60-MILS AT ALL MEMBRANE SEAMS, EXTEND MINIMUM 1" ON EACH SIDE OF JOINT



SECTION @ BALCONY SHEET MEMBRANE SERIES WATERPROOFING - LAP DETAIL

ZERO-SLOPE BALCONY DECK

© POLYGUARD PRODUCTS, INC.

SOME MATERIALS SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75119 Phone: 214-515-5000 Web Site - www.polyguard.com

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us.

NOT TO SCALE
EFFECTIVE DATE:
06/14/2021
SUPERCEDES:
04/08/2020