





CONCRETE SLAB

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET APPLIED OVER POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL

EXTRUDED CONCRETE T-RAIL, SCREW WITH DRIP EDGE TO DECK

THIS TIE-IN DIMENSION CAN BE GREATER TO ACCOMMODATE RAILING INSTALLATION DISCUSSIONS

60-MIL ELASTOMERIC SHIM (BY OTHERS)

POLYGUARD DETAIL SEALANT PW OR LM-95 APPLIED AND TOOLED FROM 30 MILS TO ZERO AS A FEATHERED EDGE, EXTEND A MINIMUM 1" ONTO EACH SIDE OF BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET AS TERMINATION EDGE SEAL

POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING STARTER STRIP APPLIED HORIZONTALLY WITH VERTICAL TURNDOWN LEG OVER POLYGUARD 650 LT LIQUID ADHESIVE OR CALIFORNIA SEALANT APPLIED AT A RATE OF 250 - 300 SF / GAL, OR OVER 650 WB LIQUID ADHESIVE APPLIED AT A RATE OF 350 - 400 SF / GAL; EXTEND BEYOND DRIP EDGE MINIMUM 2" FOR TIE-IN ADHESION OF POLYGUARD BALCONY SHEET MEMBRANE SERIES WATERPROOFING FIELD SHEET AS SECONDARY WATERPROOFING SEAL

DO NOT USE POLYGUARD EDGE SEAL AT THIS LOCATION

DRIP EDGE

EXTERIOR FACADE (BY OTHERS) - STUCCO SHOWN

MECHANICALLY-ATTACHED SHEET AIR BARRIER MEMBRANE (BY OTHERS)



SECTION @ BALCONY SHEET MEMBRANE SERIES WATERPROOFING - EDGE (OPTION 1)

© POLYGUARD PRODUCTS, INC.

SOME MATERIALS SEPARATED FOR CLARITY

Polyguard Products, Inc. P.O. Box 755 - Ennis, TX 75120 Phone: 214-515-5000 Web Site - www.polyguard.com

The information provided is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all data sheets, statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all quodes supplied by us.

NOT TO SCALE
EFFECTIVE DATE:
11/08/2021
SUPERCEDES:
09/02/2021