

MATERIALS CHECKLIST

POLYGUARD[®] COMMERCIAL STRETCH

WATERPROOFING SYSTEM: BELOW-GRADE FLUID-APPLIED MEMBRANE

Polyguard Commercial Stretch

Commercial Stretch is a fluid-applied coating used primarily to waterproof below-grade walls. It can be applied in temperatures between -20°F (-29°C) to 120°F (49°C), at an application thickness of 60 mils wet, and a coverage rate of 27 SF per gallon. It is available in VOC formulations for 525, 400, and 100.

Check		Part Number	Unit Size	Units/pallet	Wt/unit
	Polyguard Commercial Stretch				
		STRETCH GRAY 05	5-gallon pail	36 pails/pallet	48#/pail
		STRETCH GRAY 55	55-gallon drum	4 dr/pallet	445#/dr
	Commercial Stretch System Components (where applicable):				
		Part Number	Unit Size	Units/pallet	Wt/unit
	Detail Sealant PW™ • 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
	Detail Sealant PW™ • 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3 gallon pail	36 pails/pallet	37#/pail
	Required Drainage Accessories:				
	<i>Choose one of the Polyguard Drainage Products</i>				
		Part Number	Unit Size	Units/pallet	Wt/unit
	Polyflow [®] 10	POLYFLOW10	4' x 50' roll	7 rolls/pallet	38#/roll
	Polyflow [®] 10P	POLYFLOW10P	4' x 50' roll	7 rolls/pallet	38#/roll
	Polyflow [®] 15	POLYFLOW15	4' x 50' roll	7 rolls/pallet	39#/roll
	Polyflow [®] 15P	POLYFLOW15P	4' x 50' roll	7 rolls/pallet	40.5#/roll
	Possible Drainage Accessories:				
		Part Number	Unit Size	Units/pallet	Wt/unit
	Totalflow™	TOTAL FLOW	24" x 50' roll	12 rolls/pallet	30#/roll
	Totalflow™ End Outlet (4")	OUTLET4-UNIV	N/A	N/A	N/A
	Totalflow™ Tee Outlet (4")	TEE4-UNIV	N/A	N/A	N/A
	Quick Grip Spray Adhesive	QGADH30	30# canister covers approximately 1000 SF		

Weights listed are estimates.