

MATERIALS CHECKLIST

POLYGUARD[®] SPECIALTY SHEET MEMBRANES

WATERPROOFING SYSTEM: SPECIALTY SHEET MEMBRANES

Polyguard NW-75 Membrane

NW-75 Membrane is an asphalt overlay material for new and remedial bridge deck and pavement work. Mechanical and adhesive bond protects asphalt substrates from moisture and reflective cracking. Designed to be topped with a minimum 2" thickness of 280°F (138°C) to 300°F (149°C) asphalt.

Check	Polyguard NW-75 Membrane <i>*Accessories may be required – contact Polyguard Products</i>	Part Number	Unit Size	Units/pallet	Wt/unit
		NW7548	48" x 50' roll (1 roll/ctn)	25 ctns/pallet	65#/ctn

Polyguard Deckguard[®] HT

Deckguard[®] HT is designed as a high temperature underlayment (260°F) for under shingles, tile, or standing seam metal roofing.

Check	Polyguard Deckguard [®] HT <i>*Accessories may be required – contact Polyguard Products</i>	Part Number	Unit Size	Units/pallet	Wt/unit
		DGHT36	36" x 75' roll (1 roll/ctn)	36 ctns/pallet	65#/ctn

Polyguard Tileguard[™]

Tileguard[™] is designed as a reflective crack underlayment for ceramic tile.

Check	Polyguard Tileguard [™] <i>*Accessories may be required – contact Polyguard Products</i>	Part Number	Unit Size	Units/pallet	Wt/unit
		TI37	37" x 63.3' roll (1 roll/ctn)	36 ctns/pallet	65#/ctn