

POLYFLOW[®] BD

Sheet Molded Drainage For Balconies

PRODUCT NAME

Polyflow[®] BD

MANUFACTURER

Polyguard Products, Inc.
Ennis, TX 75119
(214) 515-5000
www.polyguard.com

PRODUCT DESCRIPTION

Polyflow[®] BD (Balcony Drain) is a sheet molded drain that establishes predetermined pathways for balcony water management. The fabric allows the water to flow to designated drainage exits. The punched core increases the overall release of water from within the system. Polyflow BD Sheet Molded Drainage is designed for balcony deck applications only.

BASIC USES

Basic uses include the following:

- Drainage for balcony decks with less than 3" of concrete and foot traffic only.

COMPOSITION AND MATERIALS

Polyflow[®] BD Sheet Molded Drainage Mat is manufactured with a geo-composite of a formed pre-punched impermeable polymeric core covered on both sides with a non-woven filter fabric.

TECHNICAL DATA

See physical properties table.

HORIZONTAL INSTALLATION

Clean horizontal surface of loose debris and unroll Polyflow[®] BD fabric side up.

For horizontal deck installation, Polyflow[®] BD Sheet may be loosely laid directly over the balcony waterproofing membrane. Edges of the core with the flange should be at higher side of the deck or plaza, away from any drains.

Install Polyflow[®] BD onto horizontal substrate surface,

to be drained, with an adhesive compatible with balcony waterproofing membrane substrate, or use temporary ballast to hold drain in place during the placement of the deck surface.

For overlaps, place adjacent panels so the core flange overlaps and shingles in the direction of flow to the drain collection system, scuppers, or daylight.

Butt adjacent panels together and shingle the non-woven fabric, one fabric over another.

SAFETY

SDS documents for all Polyguard products can be obtained at our website www.polyguard.com. Call Polyguard Products, Inc. at 214.515.5000 with questions.

WARRANTY

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product are beyond our control; such as weather, workmanship, equipment utilized and prior condition of the substrate. We will replace at no charge product proved to be defective within twelve (12) months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. A five (5) year material or system warranty may be available upon request. Contact Polyguard Products, Inc. for further details.

TECHNICAL SERVICES

Technical assistance, information and Polyguard's products are available through a nationwide network of distributors and architectural representatives, or contact Polyguard Products, Inc.

P.O. Box 755, Ennis, TX 75120-0755

Sales: (615) 217-6061 • Tech Support: (214) 515-5000

Email: archtech@polyguard.com

Website: www.polyguard.com

Product Data Sheet

PROPERTY	TEST METHOD	TYPICAL VALUE
<u>DRAIN PROPERTIES</u>		
FLOW CAPACITY	D 4716	12.5 g/min/ft
ROLL LENGTH	-	50 ft.
ROLL WIDTH	-	4 ft.
ROLL WEIGHT	-	35 lbs.
<u>CORE PROPERTIES</u>		
MATERIAL	-	Polymeric
THICKNESS	D 1777	0.31 inch
COMPRESSIVE STRENGTH	D 1621	5,200 lbs/ft ²
POLYMERIC FILM LAYER	-	No
<u>FABRIC PROPERTIES</u>		
MATERIAL	-	Non-Woven
GRAB TENSILE STRENGTH	D 4632	100 lbs.
CBR PUNCTURE STRENGTH	D 6241	250 lbs.
EOS (AOS)	D 4751	70 US Sieve
FLOW RATE	D 4491	140 g/min/ft ²

PACKAGING DRAINAGE & ACCESSORIES	PART NUMBER	UNIT SIZE
POLYFLOW® BD	POLYFLOW BD	4' x 50' roll
BALCONYGUARD™ SYSTEM	BALCONY GUARD 48	48" x 50' roll
650 MEMBRANE SYSTEM - 36" (For Balcony Applications Only)	650L36	36" x 66.7' roll
650 MEMBRANE SYSTEM - 48" (For Balcony Applications Only)	650L48	48" x 50' roll
650 LT LIQUID ADHESIVE	650-5 LIQ ADH 5 GA	5 gallon pail
650 LT LIQUID ADHESIVE	650-5 LIQ ADH 1 GA	4 - 1 gallon pails/ctn
CALIFORNIA SEALANT	CALSEAL5	5 gallon pail

The information contained in this document is based on data and knowledge considered to be true and accurate at time of printing and is offered for the users' consideration, investigation and verification. Polyguard Products, Inc. cannot be held liable for errors made as a result of information herein. Changes and modifications can be made to this document without prior notice. No statement, recommendation or suggestion is intended for use which would infringe on patents or copyrights held by Polyguard Products, Inc.

P.O. Box 755, Ennis, TX 75120 • PH: (214) 515-5000

www.Polyguard.com

Polyflow BD R01.07.22