



RG-2400 - Product Matrix

		Minimum Temperature	Maximum Constant Temperature	Chilled Water	Sub-Freezing Systems (ammonia, glycol, brine)	In-Service Hot Application (150F-240F)	High Temp Service (250-350F)	Spray Application	Structural Steel	Tank Chimes	COLD VESSELS	HOT VESSELS	Notes:
STANDARD GEL PRODUCTS	RG-2400 LT Low Temperature service gel	None	250° F	1	1	3	4	1	3	3	1	3	Temp Range 250°F Gels do not cure and have to be protected. For new or corroded Pipes
	RG-2400 NP Low Temperature service gel	None	230° F	1	1	3	4	1	3	3	1	3	Temp Range 230°F Gels do not cure and have to be protected. For New Piping
	RG-2400 AK In-service hot applications and tank chime installation	None	250° F	2	2	1	4	3	3	1	2	2	Temp Range 250°F - good for application on in-service HOT lines
	RG-2400 ET High temperature service	None	350° F	3	2	2	1	2	3	2	3	1	Temp Range 350°F Gels do not cure and have to be protected

SPECIALTY PRODUCTS	RG-CHW Designed for chilled water only	33° F	130°-140° F	1	4	4	4	2	3	4	4	4	Temp Range 40° F - 100° F <u>DO NOT FREEZE</u>
	RG-CSA Not a Gel Product, will harden	-20° F	200° F	N/A				1	1	N/A		2	Hardening topcoat for structural steel valves, uninsulated vessels (can be tinted)
	RG-2401 Down Hole Oil Well Corrosion Gel	None	250° F	N/A									Used for annular space corrosion control where specific gravity is an issue

MISC PRODUCTS	RG Cleaner Cleaner Designed for gels	35° F	150° F	2	1	1	2	N/A		1	1	Cleaning of tools, spills, spray equipment
	GeoWrap Geotextile for high temp uses	-40° F	350° F	2	1	1	2	N/A		1	1	Used to keep the insulation clean for inspection cycles
	UV Wrap UV wrap for uninsulated pipes	-40° F	150° F	2	2	4	3	N/A				Spiral wrap UV stretch film for protecting RG on small diameter uninsulated piping
	AlumaWrap Weather Barrier Protection for RG	-40° F	200° F	1	1	2	3	N/A	1	1	2	For uninsulated small diameter pipes to protect from UV, dirt, and personnel
	VaporGuard Self adhesive butyl sealant for use in Vapor Stops, Expansion Joints, and terminations on ammonia systems.	25 MILS	150° F	1	1	N/A				2	N/A	Available in 1-1/4" and 12" widths. See data sheet for detail drawings of proper use.
	AccuTrowel Tools to Install RG Accurately	N/A		1	1	1	1	N/A				Tool Set custom designed for 2" - 12" Pipes to apply gel at 25 MIL thickness

1 = BEST	2 = GOOD
3 = NOT RECOMMENDED	4 = WILL FAIL

WWW.RG2400.COM

214-515-5000

