

601 ZERO VOC LIQUID ADHESIVE

DESCRIPTION:

POLYGUARD 601 ZERO VOC LIQUID ADHESIVE is a fast drying, rubber-based adhesive which is used in conjunction with Polyguard pipeline coatings and tapes. This product is formulated with VOC exempted solvents to meet all California VOC regulations.



PHYSICAL PROPERTIES	TYPICAL RESULTS
Solids Content	Approximately 14 %
Flash Point	21°F (-5.9°C) Pensky Marten CC
Viscosity	800-1000 cps @77°F
Shelf Life	1 Year*
Temperature Ranges	At Application 25° to 130°F (-4° to 54°C) ** In Service -25° to 150°F (-32° to 66°C)
Storage conditions	50 to 140°F (-40 to 60°C)

*Shelf life can vary based on storage conditions.

**Material must be at or above 50°F at time of application.

APPLICATION:

601 ZERO VOC LIQUID ADHESIVE may be applied with roller or brush to a clean, dry and properly prepared pipe surface. It should be applied at an average rate of 400 ft²/gallon (10m²/liter). **DO NOT THIN LIQUID ADHESIVE.** In the event of cold weather, store inside prior to use.

SAFETY DATA SHEET

All **Polyguard Products** Material Safety Data Sheets (MSDS) and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use, health, safety, and disposal of the product.

TECHNICAL SERVICE:

Polyguard Products Inc.

PO Box 755
Ennis, Texas 75120-0755
PH: (281) 580-5700
www.polyguard.com

X:/PGP/Mktg./Lit/Pipeline/601 Zero VOC Liquid Adhesive.doc R033121

P.O. Box 755
Ennis, TX 75120
PH: (214) 515-5000
FX: (972) 875-9425

This information is based on our best knowledge, but
POLYGUARD cannot guarantee the results to be obtained.

www.Polyguard.com



Polyguard is ISO 9001 certified since 1996.