

AccuTrowel DATA SHEET



Application

Glove RG-2400® on the pipe until you cannot see the substrate. Using the proper trowel size, place the AccuTrowel on the pipe holding it at a **90 degree angle**. Slide the AccuTrowel down the pipe removing excess from the trowel as required and put it back in the bucket, or on the next section of pipe. Repeat the process around the entire pipe. Use a small amount of RG excess build up from the trowel to smooth out the trowel tracks.

Some pipe may come to the jobsite egg shaped or slightly oval in shape. The AccuTrowel may not fit odd-shaped or out of spec pipes very well.



Benefits

Install RG-2400 *Accurately!*

- Save labor
- Eliminate excess application
- No guessing about applied thickness
- Accurate 25 mil thickness
- Pipe sizes 2" - 12"
- T-304 Stainless steel construction

Sizes

- Full Set includes 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"

X:/PGP/Mktg/Lit/Mech/2019 AccuTrowel Data Sheet.doc R042821



P.O. Box 755
Ennis, TX 75120
PH: (214) 515-5000
FX: (972) 875-9425

This information is based on our best knowledge, but POLYGUARD cannot guarantee the results to be obtained.

Proud Member of
NIA National Insulation Association®

www.polyguard.com/mechanical