

600 LIQUID ADHESIVE

DESCRIPTION:

POLYGUARD 600 LIQUID ADHESIVE is a fast drying, low solids, rubber-based adhesive used in conjunction with **Polyguard** pipeline coatings. It is available in solvent systems that conform to most local VOC requirements.



PHYSICAL PROPERTIES	TYPICAL RESULTS
Solids Content	19%
Flash Point	33°F (0.5°C) TCC
Viscosity	300-500 cps @ 77°F
Shelf Life	3 Years *
Temperature Ranges:	At Application 25° to 130°F (-4° to 54° C) In Service -25° to 190°F (-32° to 77° C)
Storage conditions	-40 to 140°F (-40 to 60°C)

*Shelf life can vary based on storage conditions.

APPLICATION:

600 LIQUID ADHESIVE may be applied with roller or brush to a clean, dry and properly prepared pipe surface. It should be applied at an average rate of 400ft²/gallon (10m²/liter). **DO NOT THIN LIQUID ADHESIVE.** In the event of cold weather, store inside prior to use.

The liquid adhesive is an industrial coating and may be harmful or fatal if swallowed or enters airways. Under OSHA standard 29 CFR 1910.1200, this material is classified as a category 2 flammable liquid. Keep material away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking while applying this product. Solvents present in this product can cause serious eye irritation. In case of contact with eyes, flush with water for several minutes and contact physician.

Avoid prolonged contact with skin and breathing of vapor or spray mist from liquid adhesive. In confined areas, use explosion proof ventilation equipment. Wear all appropriate personal protective equipment.

This material is sold by **Polyguard Products, Inc.** only for the purposes described in this literature. Any other use of the products is the responsibility of the purchaser and **Polyguard Products** does not warrant nor will be responsible for any misuse of these products. **Polyguard Products** will replace material not meeting our published specifications within one year from date of sale.

SAFETY DATA SHEET:

All **Polyguard Products** Safety Data Sheets (SDS) and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use, health, safety, or disposal of the product.

TECHNICAL SERVICE:

Polyguard Products Inc.

Ennis, Texas 75120-0755

PH: (281) 580-5700

www.polyguard.com

X:/Lit/Pipeline/600 Liquid Adhesive.doc R.101521

P.O. Box 755
Ennis, TX 75120
PH: (281) 580-5700

This information is based on our best knowledge, but
POLYGUARD cannot guarantee the results to be obtained.

www.Polyguard.com



Polyguard is ISO 9001 certified since 1996.